

RODIM Soft Pad

Published: 01.04.2019

Latest update: 01.04.2019

SANDING



Available in:

Article Number	Article description
45225085	ROD-408101 Soft Pad F 115x140mm (20)
45225086	ROD-408102 Soft Pad SF 115x140mm (20)
45225087	ROD-408103 Soft Pad UF 115x140mm (20)

Packing:

1 Piece = 1 Pack consisting of 20 Pads

Application

hand sanding (dry and wet) of wood, paint, metal, glass fiber, coatings and composites

Foam Type

MDI based grey polyurethane

Density

85 kgm³

Tear strength

370 Nm-1

Tensile strength

290kPa

Adhesive

Synthetic polymer/resin system

Topcoat

Cross-linked synthetic polymer system

Abrasive grit

Aluminum oxide

RODIM Soft Pad

SANDING

Intended Use

This product is supplied for hand use only as an abrasive sander. Both dry and wet sanding.

Physical Properties

Appearance:	Grey cellular solid foam with a dark grey abrasive coating.
Foam density:	75 kg/m ³ ,
Tensile Strength:	273 KPA
Auto ignition temp:	>200 C
Conditions to avoid:	Open flames, intense heat sources, Temperatures in excess of 200C.

On no account should they be disposed of by burning as fires involving polyurethane foam produce dense black smoke and toxic gases.

Materials to avoid: Strong oxidizing agents

This product does not contain any residual isocyanate or blowing agent but may contain traces of catalyst and surfactants.

Storage

It is recommended that all sponge Abrasive products should be stored at constant levels of temperature and humidity within the ranges of 18 - 22 C. They should be kept away from damp (or cold) walls or floors to avoid possible moisture absorption. Equally storage adjacent to heat sources e.g. steam pipes, radiators, hot air ducts, ovens etc. should be avoided.

Products should be retained in their original packing until immediately prior to use.