

Smartmasking Plus Recycled

Published: 26.06.2023

Latest update: 26.06.2023

MASKING



Masking Film

with more than 30% recycled plastic

Temperature stability until
125°C

Storage Remarks

Storage time is 12 months from delivery date. Keep storage temperature between + 20° C / ± 10° C and the relative humidity by 30 – 90%. Storage in closed rooms. Avoid exposure of UV-radiation.

Available in:

Article number	Article description
45247405	ROD-305503 Smartmasking+ Recycled 4m x 150m
45247394	ROD-305504 Smartmasking+ Recycled 6m x 100m

Packaging:

1 Piece per box

Properties:

Property	Value & measuring unit	Measuring Method
Density	Ca. 1,07 g /cm ³	DIN EN 1183
Thickness	14 µm	GPA (Thickness Profile)

Smartmasking Plus Recycled

MASKING

Property	Value & measuring unit	Measuring Method
Tensile Strength machine direction	>25 N / mm ²	ASTM D 882
Tensile Strength transverse direction	>20 N / mm ²	ASTM D 882
Dart drop	50g	ASTM 1709-91
Temperature stability	Until 125° C	

This technical information has been given to the best of our knowledge. The above-mentioned standards are average values and no granted assurance of special properties. This statement is limited to the material, in the state as it leaves the manufacturer and does not include possible modifications by conversion and/or handling after dispatch.