Published: 01.09.2026
Last update: 01.09.2026

RODIM® by Surventis

**Technical Data Sheet**

# RODIM PERFORATED LIFTING TAPE

## Application

- Use for masking jobs on hard to reach places such as edges, corners and gaps.
- Protects rubber trims and bodyside moldings during spraying, e.g.:
  - Masking rubber around flush fitted car windows.
  - Masking rubber around sun proofs.
  - Masking gaps between body parts.
- Recommended application temperature between +15°C to +30°C. Service temperature -20°C to +120°C after application.
- Highest performance will be reached after a bonding period of 24 hours at +23°C.
- Apply on a clean, dust free and grease free surface.

## Properties

- Size: 50 mm x 10 m
- 10 mm reinforced PET film
- Perforated each 50 mm

## Performance

- Easy to handle and quick in application.
- Highly flexible to follow contours which fit all parts of the car.
- High temperature resistance

## Storage and shelf life:

- Store in a clean, dry and well-ventilated area at a temperature between 10°C and 30°C to ensure optimal product performance and shelf life.
- When stored under these recommended conditions, the product has a shelf life of 24 months from the date of manufacture.

## Packaging

- 36 PCS = 36 ROLLS = 1 CARTON

| Article no. | Article description |
|---|---|
| 2045003524 | ROD-302202 PERF. LIFTING TAPE 50MMx10M |

## Technical Specifications

- Thickness 0.17 mm
- Adhesive strength 9 N / 25 mm
- Tensile strength 118 N / 25 mm
- Service temperature range -20°C to +120°C
- Elongation 12%
- PET film 10 mm